

MASTRO SERIES

API SN 5W-30

Description

Eton Motor Oils are designed with high-quality synthetic base stocks and top-of-the-line additive technology to provide maximum protection for today's modern engines and are formulated to meet the common requirements for U.S., European, and Japanese cars and light trucks with gasoline engines. Eton Full Synthetic 5W-30 Motor Oil Recommended for use in cars and light trucks with gasoline and gasoline turbocharged engines where API SN and all prior specifications are required.

Features

- Most advanced chassis formula for high performance engines
- Provide higher levels of cleaning and protection
- Helps to improve and retain fuel economy
- Protects vehicle emission system and turbo charge components
- Proven performance across a variety of driving conditions and temperatures



TECHNICAL CHARACTERISTICS – API SN 5W-30

TESTS	PRODUCT	SAE 20W30 API SN
	METHOD	
Appearance	Visual	C/B
Colour	ASTM-1500	Golden L2
Water	HOT PLATE	Nil
Sp.Gravity @15 deg c	D1298	0.865
Viscosity @ 100 deg C,cSt	D445	11-12
Viscosity @40 deg C,cSt	D445	80
Viscosity Index	0	>155
Flash Point, COC, deg C	D92	220
TBN, mgm KOH / gm	D2896	>8
Pour Point deg C	D97	<-30
Foam Seq.I/II/III,ml	D892	0/0/0