

MASTRO SERIES

API SN 5W-40

Description

Best for modern gasoline and diesel engines with and without exhaust gas turbochargers. For the protection and value retention of the engine during long intervals between oil changes and with high loads. Low-viscosity high-tech low-friction motor oil with high shear stability. Combined with innovative additive technology and the special additives. Reliably prevents the formation of deposits, reduces frictional losses in the engine and provides optimum protection against wear. The results are savings in fuel and an extended service life for the engine.

Features

- Helps remove sludge from dirty engines
- High viscosity to reduce leaks in older, high-mileage engines
- Designed to provide consistent engine performance
- Features High Resistance to Foaming and Corrosion
- Provides superior low to high-temperature performance



TECHNICAL CHARACTERISTICS – API SN 5W-40

TESTS	PRODUCT	SAE 5W40 API SN
	METHOD	
Appearance	Visual	C/B
Colour	ASTM-1500	Golden L2
Water	HOT PLATE	Nil
Sp.Gravity @15 dg c	D1298	0.865
Viscosity @ 100 deg C,cSt	D445	14-15
Viscosity @40 deg C,cSt	D445	103
Viscosity Index	0	>140
Flash Point, COC, deg C	D92	220
TBN, mgm KOH / gm	D2896	>8
Pour Point deg C	D97	<-24
Foam Seq.I/II/III,ml	D892	0/0/0